



Waagrecht und senkrecht
einsetzbar
Horizontal and vertical use

Typ „Picco“

PTC Heizung / *PTC Heating*

Ausführungen / Performances:

Leistungen <i>Power</i>	Spannungen <i>Voltage</i>	Maße <i>Dimension</i>	Anschluss <i>Connection</i>	Artikel Nr. // Art. No. <i>ohne Lüfter / without fan</i>
15 W 20 W 50 W 70 W	110-265 V AC/DC 110-265 V AC/DC 110-265 V AC/DC 110-265 V AC/DC	X 73x40x47mm 73x40x47mm 102x40x47mm 102x40x47mm	Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ²	01401520Kb0 01402020Kb0 01405020Kb0 01407020Kb0
15 W 20 W 50 W 70 W	10-60 V AC/DC 10-60 V AC/DC 10-60 V AC/DC 10-60 V AC/DC	73x40x47mm 73x40x47mm 102x40x47mm 102x40x47mm	Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ² Kabel / <i>Cable</i> 2x0,75mm ²	01401510Kb0 01402010Kb0 01405010Kb0 01407010Kb0

Montage / mounting: Clip für DIN Hutschiene EN 60715
clip for DIN rail EN 60715

wahlweise Schraubbefestigung
optional screw fixing

Anschlussplan / Connection:

